

TECHNICAL DATA SHEET

Item name: Anti-slip tape 50mmx0.8mmx15M
Item No.: 37281



Material: sanded PVC film
Material of sand: corundum

Technical data:

Glue: solvent based rubber glue
 Foil thickness: 150Mic
 Total thickness: 800Mic
 Release film: White PE-coated Silicone Release Paper
 Release film thickness: 120Mic
 Adhesion of tape: very good

PROPERTIES	UNIT	VALUE	TEST METHOD
Persistent strength	H.25 mm	≥ 24	PSTC-7
180 °C Peeling strength	N/25 mm	4,5	PSTC-1
Tensile strength	N/25 mm	50	PSTC-31
Elongation	%	180	PSTC-31
Tear resistance	N	50	ASTM D-732
Water resistant	Month	≥10	
UV resistant	/	Yes	
Fire resistant	Class	V-0	UL94
Moisture resistant	Month	≥8	
Application temperature	°C	0 ~ +40	
Temperature resistance	°C	-30 ~ +80	

Characteristics:

The anti-slip tape is a self-adhesive tape made of soft PVC fitted with adhesive on one side and anti-slip side with rugged PVC suitable for barefoot.

Use:

The anti-slip tape serves as slip protection on a wet or otherwise slippery surface such as a slip on the stairs. An anti-slip tape will help protect your health and the health of other people in your surroundings.

The surface must always be clean, dry, free of dust, grease and oil.