

THE GUN ON THE BOTTOM OF A CAVITY (48036)



The gun with a fixed nozzle for spraying a protective tube for the chassis and the spraying of the vehicle body.

Description:

- * The preservation of cavities and underbody protection against corrosion
- * The common screw cartridge

Surface Protection: Apply to the surface under the pressure of 2-8 bar at a distance of 20-30 cm. The width and strength of layer regulate air pressure, spraying distance and speed.

Technical data:

- * Working pressure 2 - 8 bar
- * Air consumption 180 l/min
- * Connection 1/4"
- * Weight 0,4 kg

Important safety instructions

1. First Toxic fumes generated during spraying of the material can form intoxication and seriously damage health. Always wear protective goggles, gloves and use a respirator to protect against toxic fumes. Avoid contact with skin color and eyes (Fig. 4)
2. Never use oxygen or other gas cylinder as a pressure source because of the possibility of an explosion and subsequent injuries (Fig. 3)
3. Paint and paint thinner can be highly flammable. Work with them because in a well ventilated room and avoid ignition (do not use near open flame, smoke, etc.), (Fig.2)
4. Before performing maintenance in a period of non-product, unplug the product from the pressure hose.
5. Use a clean, dry, regulated compressed air in the range from 2.5 to 3.5 bar. Never exceed the maximum pressure of 6 bar (Fig. 1)
6. Use only components recommended by the manufacturer.
7. Before use, make sure all screws and container are properly tightened to prevent leakage of color.
8. Before use, check the trigger and nozzle due to the proper functioning of the product.
9. Never clean solutions halogenated hydrocarbons (for example: trichlorethan, methylene chloride) or acid or lye, which can chemically react with aluminum and galvanized parts.
10. Never modify a tool for others to use.

